

PRODUCT INFORMATION

Cogan Condo Lockers

2946 Larimer St. Denver, CO 80205 303-295-1100 / 800-373-7693 FAX 303-295-2464 Email info@snyderequipment.com www.snyderequipment.com

door opening

BETTER.

MATERIAL

- MESH PANELS ARE MADE OF UN-FRAMED ELECTRO-GALVANIZED WELDED WIRE MESH 6GA & 8GA WITH OPENING OF 2"X 2". TRANSOM ANGLES ARE MADE OF 1 1/8"X 1 1/8" X 12GA HEAVY DUTY STRUCTURAL STEEL. ROOF MESH IS MADE OF 2" X 4" X 10GA WELDED WIRE MESH.
- DOORS FRAMES ARE MADE OF ANGLE 1 1/8"X 1 1/8" X 12GA HEAVY DUTY STRUCTURAL STEEL, SHAPED FOR EXTRA STRENGHT. CORNERS ARE NOTCHED AND SEAM-WELDED. WELDED WIRE MESH IS 2"X 2"X 10GA (0.134), RESISTANCE WELDED TO THE FRAME AT EVERY 6". DOORS ARE RE-INFORCED WITH ONE 1/2" DIAMETER ROD. DOORS SHALL BE EQUIPED WITH A SET OF PADLOCK HASPS, TWO DOOR STOPPERS AND TWO PAIR OF STEEL PIN HINGES.
- POSTS ARE MADE OF ELECTRO-GALVANIZED 1 1/2" X 1 1/2" X 17GA SQUARE SEAM WELDED, ENGINEERED FOR PERFECT SUPPORT AND RIGIDITY WITH 3" X 5" X 1/4" ZINC PLATED BASEPLATES.
- ALL NECESSARY ASSEMBLY FASTNERS SHALL BE PROVIDED. ANCHORS ARE NOT PROVIDED BY COGAN.
- FINISH ELECTRO-GALVANIZED



