

SNYDER

Equipment, Inc.

Storing, Rolling, Lifting since 1947



PRODUCT INFORMATION

Enpac Stinger Berms

2946 Larimer St. Denver, CO 80205
303-295-1100 / 800-373-7693
FAX 303-295-2464
Email info@snyderequipment.com
www.snyderequipment.com



AIRE-STINGER BERM™

THE BUZZWORD IN LARGE, AGGRESSIVE AND IMMEDIATE SPILL RESPONSE.



The ENPAC Corporation AIRE-Stinger Berm™ allows for one-time set-up and then continual drive-in and out without ever having to set down the end sidewalls. Uses unique patent pending combination of foam ends and snap-up sidewall supports mounted on the exterior; there is nothing to interfere with the interior berm space or present decontamination concerns. The fuel/chemical resistant containment area is constructed with patented hot-air welds producing tension-relieved corners, integrated sidewall support sleeves and drains. The Foam Sidewall system consists of urethane (fed. Spec. PPP-C-1752D, Type 1, Class 1, Grade A) encased in a fuel/chemical resistant membrane cover. The sidewall design incorporates high strength connectors and a two way air relief system that facilitates automatic entry / exit without assistance. The foam sidewalls collapse in either direction and snap back automatically to their upright position. The foam logs are utilized on the entry / exit so that a tanker can be driven in or out at will. The AIRE-Stinger Berm is manufactured and tested to ASTM-D751, D1117, D2136, D1204, D3384, D1149, D543, D3083, G-26. The AIRE-Stinger Berm is made out of rugged and resistant 30 oz./32 MIL fabric material. Custom sizes available, standard color is black.

	4820-BK-SF	4836-BK-SF	4854-BK-SF	4860-BK-SF	4885-BK-SF
Exterior Dimensions	10' W x 26' L x 1' 30cm	12' W x 36' L x 1' 30cm	14' W x 54' L x 1' 30cm	12' W x 60' L x 1' 30cm	14' W x 85' L x 1' 30cm
Weight	117 lbs. / 53kg	170 lbs. / 77kg	252 lbs. / 114kg	245 lbs. / 110kg	420 lbs. / 190kg
Sump Capacity	1,944 gal. / 7,358 liters	3,231 gal. / 12,231 liters	5,655 gal. / 21,406 liters	5,385 gal. / 20,384 liters	8,901 gal. / 33,693 liters
Regulations	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water





STINGER BERM™

ENPAC's new Stinger Berm™ leads the industry with its wide range of sizes and capacities for large-scale spill containment. Stinger Berm's flexible sidewalls and easy-to-assemble snap-up design allows immediate response for industrial, government, construction, transportation and emergency response applications. The Stinger Berm's flexible sidewall design provides quick setup and allows compact fold-up, storage and transport. Stinger Berms feature excellent rip, tear and puncture resistance for the most demanding application or terrain. Ground pad and Track Mat provide additional protection.

As an industry innovator, ENPAC can design, develop and manufacture berms in sizes to fit any application. Contact ENPAC for help with your application.

Stinger Berm Features and Benefits

- Tension-relieved radius corners: Virtually eliminates stresses on corners and failures caused by drive-in/drive-out, filling, and use.
- Replaceable stays: Instant field sidewall support replacement and repair avoids costly and difficult field welding and protects your critical schedule that could otherwise be affected by downtime delays and additional costs.
- Field fabric repair kit: Provides instant peel & stick fabric repair to help protect against spills associated with minor tears or rips, protecting schedules and holding down project costs.
- All containment welds air-lance tested in manufacturing at 60 psi: Your assurance that the product is going to work first time, every time.
- All product proof tested at the factory: Your further assurance that the product is ready for your tough application.
- Product is CAD designed and CAD cut: Each new unit is exactly like the one before it, each and every time.
- Each berm is individually serial numbered: Provides traceability for quality control.
- 10-Year Environmental Effects Warranty: Assures long life and usability.
- Accept no substitutes: Demand the Stinger Berm's unique features and benefits that protect your bottom line.

	4801-BK-SU	4802-BK-SU	4803-BK-SU	4804-BK-SU	4805-BK-SU
Exterior Dimensions	4' W x 4' L x 8" H	4' W x 4' L x 12" H	4' W x 6' L x 8" H	4' W x 6' L x 12" H	4' W x 8' L x 8" H
	1.22 m x 1.22 m x 20 cm	1.22 m x 1.22 m x 30 cm	1.22 m x 1.83 m x 20 cm	1.22 m x 1.83 m x 30 cm	1.22 m x 2.44 m x 20 cm
Weight	11 lbs. / 5 kg	25 lbs. / 11 kg	16 lbs. / 7 kg	36 lbs. / 16 kg	21 lbs. / 10 kg
Sump Capacity	80 gal. / 302 liters	119 gal. / 450 liters	120 gal. / 454 liters	1,749 gal. / 564 li-	160 gal. / 605 liters

				ters	
Regulations	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water
	4806-BK-SU	4807-BK-SU	4810-BK-SU	4812-BK-SU	4816-BK-SU
Exterior Dimensions	6' W x 6' L x 1' H 1.83 m x 1.83 m x 30.5 cm	8' W x 8" L x 8" H 2.44 m x 2.44 m x 20 cm	10' W x 10' L x 1' H 3.05 m x 3.05 m x 30 cm	12' W x 12' L x 1' H 3.65 m x 3.65 m x 30 cm	16' W x 16' L x 1' H 4.87 m x 4.87 m x 30 cm
Weight	36 lbs. / 16 kg	43 lbs. / 20 kg	75 lbs. / 34 kg	108 lbs. / 48 kg	192 lbs. / 87 kg
Sump Capacity	269 gal. / 1,018 liters	320 gal. / 1,211 liters	748 gal. / 2,831 liters	1,077 gal. / 4,076 liters	1,915 gal. / 7,249 liters
Regulations	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water

	4820-BK-SU	4836-BK-SU	4850-BK-SU	4854-BK-SU	4860-BK-SU
Exterior Dimensions	10' W x 26' L x 1' H 3.05 m x 7.92 m x 30 cm	12' W x 36' L x 1' H 3.65 m x 10.97 m x 30 cm	15' W x 50' L x 1' H 4.57 m x 15.24 m x 30 cm	14' W x 54' L x 1' H 4.26 m x 16.45 m x 30 cm	12' W x 60' L x 1' H 3.65 m x 18.28 m x 30 cm
Weight	195 lbs. / 88 kg	324 lbs. / 146 kg	300 lbs. / 136 kg	302 lbs. / 137 kg	225 lbs. / 102 kg
Sump Capacity	1,944 gal. / 7,358 liters	2,423 gal. / 9,172 liters	5,610 gal. / 21,236 liters	5,655 gal. / 21,406 liters	5,385 gal. / 20,384 liters
Regulations	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water

	4866-BK-SU	4885-BK-SU
Exterior Dimensions	14' W x 66' L x 1' H 4.26 m x 20.11 m x 30 cm	14' W x 85' L x 1' H 4.26 m x 25.9 m x 30 cm
Weight	359 lbs. / 162 kg	476 lbs. / 215 kg
Sump Capacity	6,912 gal. / 26,164 liters	8,901 gal. / 33,693 liters
Regulations	EPA, SPCC, Storm Water	EPA, SPCC, Storm Water

